

AC-Motoren GmbH

Graugussmotoren / Cast Iron Housing

Technische Daten / Technical data

4 polig Leerlaufdrehzahl 1500 U/min - 4 pole Synchronous speed 1500 rpm											400V / 50Hz	
ACM 160 MA-4	11,00 / 13,20	1460 / 1752	88,50	0,84	21,40	71,59	7,00	2,20	2,30	0,07470	118,0	
ACM 160 L-4	15,00 / 18,00	1460 / 1752	89,50	0,85	28,50	98,12	7,50	2,20	2,30	0,09180	132,0	
ACM 180 M-4	18,50 / 22,20	1470 / 1764	90,10	0,86	34,50	120,19	7,50	2,20	2,30	0,13900	164,0	
ACM 180 L-4	22,00 / 26,40	1470 / 1764	90,60	0,86	40,80	142,93	7,50	2,20	2,30	0,15800	182,0	
ACM 200 L-4	30,00 / 36,00	1470 / 1764	91,50	0,86	55,00	160,96	7,20	2,20	2,30	0,26200	245,0	
ACM 225 S-4	37,00 / 44,40	1475 / 1770	92,10	0,87	66,70	198,51	7,20	2,20	2,30	0,40600	258,0	
ACM 225 M-4	45,00 / 54,00	1475 / 1770	92,60	0,87	80,60	290,37	7,20	2,20	2,30	0,46900	290,0	
ACM 250 M-4	55,00 / 66,00	1480 / 1776	93,10	0,87	98,00	354,90	7,20	2,20	2,30	0,66000	388,0	
ACM 280 S-4	75,00 / 90,00	1480 / 1776	93,70	0,87	133,00	483,95	7,20	2,20	2,30	1,12000	510,0	
ACM 280 M-4	90,00 / 108,00	1480 / 1776	94,00	0,87	159,00	578,79	7,20	2,20	2,30	1,46000	606,0	
ACM 315 S-4	110,00 / 132,00	1480 / 1776	94,60	0,88	191,00	707,41	6,90	2,10	2,20	3,11000	910,0	
ACM 315 M-4	132,00 / 158,40	1480 / 1776	94,90	0,88	228,00	848,89	6,90	2,10	2,20	3,62000	1000,0	
ACM 315 LA-4	160,00 / 192,00	1480 / 1776	95,00	0,89	273,00	1029,00	6,90	2,10	2,20	4,13000	1055,0	
ACM 315 LB-4	200,00 / 240,00	1480 / 1776	95,00	0,89	341,00	1286,20	6,90	2,10	2,20	4,73000	1128,0	
ACM 355 M-4	250,00 / 300,00	1490 / 1788	95,30	0,90	421,00	1602,40	6,90	2,10	2,20	6,50000	1700,0	
ACM 355 L-4	315,00 / 378,00	1490 / 1788	95,30	0,90	530,00	2019,00	6,90	2,10	2,20	8,20000	1900,0	
ACM 400 MA-4	400,00 / 480,00	1492 / 1790	96,00	0,90	666,00	2510,00	6,61	1,92	2,75	14,95000	2786,0	
ACM 400 MB-4	450,00 / 540,00	1492 / 1790	96,10	0,90	750,00	2880,00	6,84	2,03	2,81	15,63000	3122,0	
ACM 400 LA-4	500,00 / 600,00	1492 / 1790	96,40	0,90	831,00	3203,00	6,19	1,83	2,52	18,41000	3132,0	
ACM 400 LB-4	560,00 / 672,00	1492 / 1790	96,40	0,90	924,00	3587,00	6,64	2,02	2,67	19,62000	3548,0	
ACM 400 LC-4	630,00 / 756,00	1492 / 1790	96,40	0,91	1043,00	4035,00	5,81	1,75	2,34	21,33000	3589,0	
ACM 450 MA-4	560,00 / 672,00	1492 / 1790	96,30	0,91	921,00	3570,00	6,43	1,29	2,71	35,10000	3584,0	
ACM 450 MB-4	630,00 / 756,00	1492 / 1790	96,40	0,91	1036,00	4020,00	6,94	1,47	2,90	41,00000	4055,0	
ACM 450 LA-4	710,00 / 852,00	1492 / 1790	96,40	0,91	1164,00	4530,00	6,17	1,30	2,57	41,00000	4055,0	
ACM 450 LB-4	800,00 / 960,00	1492 / 1790	96,60	0,93	1308,00	5100,00	6,91	1,53	2,28	49,50000	4724,0	
ACM 450 LC-4	900,00 / 1080,00	1492 / 1790	96,60	0,92	1469,00	5740,00	5,81	1,75	2,34	49,50000	4732,0	

Technische Änderungen und Irrtümer vorbehalten. / Technical modifications reserved, errors excepted.